



GIGASWITCH 9/20

Compact multiswitch for 20 participants for distribution of 2 orbit positions and terrestrial signals

EAN	Item no.	Colour	Weight	Weight (Box)	Box	Device (W x H x D)
4019588032552	0000/3255	blau / gelb	600 g	900 g	26.50 x 5.70 x 15.60 cm	17.40 x 3.30 x 15.00 cm

AMPLIFICATION	Nominal voltage: 230 V	Distribution length: max. 70 m
Sat: -5 dB typical	Frequency: 50 Hz	SCOPE OF DELIVERY
Terrestrial: -20 dB	Mains adapter: external 15V/1,2A	GIGASWITCH 9/20, power supply (15V/1,2A), instruction manual
Return path: -20 dB	RECEPTION RANGE	
DECOUPLING	Sat: 950 ... 2150 MHz	
Output: > 25 dB	Terrestrial: 5 ... 790 MHz	
ENVIRONMENT	TECHNICAL DATA	
Humidity: 10 ... 70 %	Satellite inputs: 8	
Ambient temperature: -25 ... 45 °C	Terrestrial input: 1	
POWER SUPPLY	Outputs: 20	
KEYFEATURES		
DiSEqC 1.0	HDTV	DVB-T2 ready